

## THE BENEFITS OF WOOL

- The unique beneficial properties of wool have never been synthetically reproduced
- Research by AgResearch has revealed that wool absorbs harmful air pollutants (such as formaldehyde, sulfur dioxide and nitrogen oxides) and does not re-emit them. It has been estimated that wool which is used in interiors can help purify the air for up to 30 years.
- Floc Cloud is hypoallergenic it is resistant to bacteria, mould and mildew that can trigger allergic reactions. It has
  microscopic pores that respond effectively to changes in humidity preventing microorganisms from growing and
  breeding.
- A by-product of ethical farming practices in New Zealand ensures the supply of quality strong-wool.
- Using Floc Cloud is a renewable, biodegradable and natural choice which provides naturally air filtering, heat and moisture regulating properties.
- Extensive research has gone into developing a product that meets fire regulations for interior linings. The solution gives a Group 1-S (according to ISO 5660 Part 1) performance and doesn't use nasty chemicals. The product is Red List free and can be buried at end of life.





V 3.0 01/24





## **Floc Cloud**

Sound absorption	<b>Thickness</b> 40 mm		<b>ΗΖ</b> αρ	<b>125</b> 0.20	<b>250</b> 0.60	<b>500</b> 0.95	<b>1000</b> 1.00	<b>2000</b> 1.00		α <sub>w</sub> 0.90	<b>NRC</b> 0.95
	*Tested to AS/ISO 3	354: 2006 Acoust	ics-Measu	rement	of sound	absorptio	on in a r	reverber	ation ro	om. A-mo	ount
Fire Test	Thickness       Class         40 mm       Group 1-S         Fire treatment is a natural product, however dust maybe present when product is handled         *Tested to ISO 5660.1-2015 Reaction to fire tests – Heat release smoke production and mass loss rate part 1 (cone calorimeter).										
Standard sizes	Thickness 40 mm						x 1112	2 (other	r sizes a	available	
	Due to the natural and face finish may				y be pres	ent. Plea	se be av	ware tha	t colour		
Custom size	ThicknessSizes40 mm1112 x 1112 (other sizes available on indent)										
Colours											
	Natural	lvory S	Sage	Ston	e	Storm		Shadow	/	Ebony	
	Due to the natural i colour and face fini					ent. Pleas	se be av	vare that	t		
Weight	4.8 kg/m <sup>2</sup>										
Density	120 kg/m <sup>3</sup>										
Edge details	Square edge										
Thermal resistance	0.35 m <sup>2</sup> K/W (calculated)										
Custom digital printing	FLOC www.internet		and the second se								
										V 3.0	01/24
T&R INTERIOR SYSTEMS	Bosk Stratozrace	ECLIPSE Vertißrace		'LO( Rid <b>lu</b>		PHC	ONIC CBI		i	)800 66 nfo@tris vww.tris	.co.nz



Sustainability				
Glasswool	Recycled product: the rate of pre-consumer recycled content in Phonic fibreglass ceiling tiles is 80%. The recycled content includes 30% industrial waste and 70% civilian used waste, all procured from reclamation depots			
Floc	Floc harnesses the sustainable nature of wool, enhancing its performance for the built environment. At end of life, it can be returned to the earth as the product is full compostable. Made from 100% New Zealand born, grown and processed strong-wool, utilising the by-product of shearing to create a sustainable acoustic wall lining			
VOC				
Glasswool	*Tested to ASTM D519-06 standard test method			
Floc	*Tested to ASTEM D5116-2017 Standard Guide for Small-Scale Environmental Chamber Determinations of Organic Emissions from Indoor Materials/Products. Test report number 1435590.3			
Warranty	30 Year product warranty when installed in accordance with NZ1170.5			
NZ Building Code	Exceeds clause B2 - durability, 5 years			

\*Test reports available upon request





V 3.0 01/24